		~
	كبصفت	000
		11
		•
		~
		Ξ
		σ
_		•
_	_	
$\overline{}$		_
	هنت بها	·
		•
_	=	70
		v
•		- 1
		-
<b>S</b>		
		-

Court story from their refers they they first they

The High

FORM PTÖ-1390 (REV 11-98) U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371

ATTORNEY'S DOCKET NUMBER

BEIERSDORF 598-WCG

U.S APPLICATION NO. (If known, see 37 CFR 1.5)

ng /445065

INTERNATIONAL APPLICATION NO.		INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED		
PCT/E	P98/03168	28 May 1998 (28.05.98)	10 June 1997 (10.06.97)		
TITLE OF INVENTION BANDAGE FOR THE ARM WITH ENCLOSURE FOR THE SHOULDER					
APPLICA	ANT(S)FOR DO/EO/US n BODENSCHATZ, Thorst				
Applicant	t herewith submits to the United States	Designated/Elected Office (DO/EO/US) the follow	ving items and other information:		
1. X	This is a FIRST submission of items	s concerning a filing under 35 U.S.C. 371.	•		
2.	This is a SECOND or SUBSEQUE	NT submission of items concerning a filing under 3	5 U.S.C. 371.		
3. X	examination until the expiration of the	al examination procedures (35 U.S.C. 371(f)) at any the applicable time limit set in 35 U.S.C. 371(b) and	PCT Articles 22 and 39(1).		
4. X		reliminary Examination was made by the 19th mor	nth from the earliest claimed priority date.		
5. <u>X</u>		ication as filed (35 U.S.C. 371(c)(2))			
		(required only if not transmitted by the Interna	tional Bureau).		
		the International Bureau.			
ر ا <del>ر</del> ا		opplication was filed in the United States Received			
6. X		Application into English (35 U.S.C. 371(c)(2)			
الــا		International Application under PCT Article			
		(required only if not transmitted by the Intern	ational Bureau).		
		y the International Bureau.	I NOT		
		wever, the time limit for making such amendn	nents has NOT expired.		
. П	d. have not been made and	•			
아 아 다		to the claims under PCT Article 19 (35 U.S.C.	. 371(c)(3)).		
9. IXI	An oath or declaration of the invo				
10.	A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).				
Items 1	1. to 16. below concern documen	nt(s) or information included:			
11. X	An Information Disclosure Stater				
12. X	An assignment document for reco	ording. A separate cover sheet in compliance v	with 37 CFR 3.28 and 3.31 is included.		
13. X					
ш	A SECOND or SUBSEQUENT preliminary amendment.				
14.	A substitute specification.				
15.	A change of power of attorney an	d/or address letter.			
16. X	Other items or information:				
a)	First page of publis	hed application, WO 98/56322			

PCT Applicant's Guide - Volume II - National Chapter - US

ng / L	25065 I	PCT/EP98/03168		BEIERSDO	RF 598-WCG
	owing fees are submitted:			CALCULATIONS	PTO USE ONLY
BASIC NATIONA	AL FEE (37 CFR 1.492 (a)				
Neither internation	ational preliminary examinational preliminary examination and search fee (37 CFR 1.44	ation fee (37 CFR 1.482)	İ		
and Internation	nal Search Report not prepa	ared by the EPO or JPO	\$970.00		
International p USPTO but In	oreliminary examination fee aternational Search Report p	e (37 CFR 1.482) not paid to prepared by the EPO or JPO	\$840.00		•
International p but internation	oreliminary examination fe nal search fee (37 CFR 1.44	e (37 CFR 1.482) not paid to US 5(a)(2)) paid to USPTO	SPTO <b>\$760.00</b>		
International p but all claims	oreliminary examination fee did not satisfy provisions o	paid to USPTO (37 CFR 1.482 f PCT Article 33(1)-(4)	) \$670 <b>.</b> 00		
International pand all claims	International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4)				_
	ENTER APPRO	PRIATE BASIC FEE AM	IOUNT =	<b>\$</b> 840.00	
Surcharge of \$130 months from the	0.00 for furnishing the oath earliest claimed priority dat	or declaration later than 20 20 (37 CFR 1.492(e)).	30	S	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	20 - 20 =		X \$18.00	<b>\$</b> 0	
Independent claims	2 -3 =		X \$78.00	<b>\$</b> 0	
MULTIPLE DEPI	ENDENT CLAIM(S) (if appli		+ \$260.00	\$ 0	
	TOTAL	OF ABOVE CALCULA	rions =	\$	
Reduction of 1/2 must also by filed	for filing by small entity, if (Note 37 CFR 1.9, 1.27, 1	applicable. A Small Entity Stat .28).	ement	\$	
		SUBT	TOTAL =	\$ 840.00	
Processing fee of months from the	\$130.00 for furnishing the earliest claimed priority dat	English translation later than e (37 CFR 1.492(f)).	20 30 +	S	
		TOTAL NATION	AL FEE =	\$ 840.00	
Fee for recording accompanied by	the enclosed assignment (3 an appropriate cover sheet (	7 CFR 1.21(h)). The assignment 37 CFR 3.28, 3.31). \$40.00 per	nt must be	\$	
		TOTAL FEES ENC	LOSED =	\$ 840.00	
				Amount to be: refunded	\$
				charged	S
a. A chec	k in the amount of \$	to cover the above	ve fees is enclose	d.	
b. X Please of A dupli	b. X Please charge my Deposit Account No. 14-1263 in the amount of \$840.00 to cover the above fees. A duplicate copy of this sheet is enclosed.				
c. X The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 14-1263. A duplicate copy of this sheet is enclosed.					
NOTE: Wher 1.137(a) or (b)	re an appropriate time lim ) must be filed and grante	it under 37 CFR 1.494 or 1.49 ed to restore the application to	5 has not been n pending status.	net, a petition to re	vive (37 CFR
SEND ALL CORRESPONDENCE TO					
02.12.1			Lall	am Me Serot	
	C. Gerstenzang	IIG DA	SIGNATI	JRE	· —
	McLAUGHLIN & MARC e Plains Road	US, P.A.	Wi11	iam C. Gerst	enzang
1	n, New York 1059	1	NAME		
	, 101K 103)	<u>*</u>	27,5	52	
			REGISTR	ATION NUMBER	
1					

09/445065 428 Rec'd PCT/PTO 0 1 DEC 1999.

Attorney Docket No. : Beiersdorf 598-WCG

: 6713-St-ar

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s):

Stefan BODENSCHATZ, Thorsten HERZBERG

Serial No.

To Be Assigned

Filed

Herewith

For

BANDAGE FOR THE ARM WITH ENCLOSURE FOR THE

**SHOULDER** 

**Art Unit** 

To Be Assigned

Examiner

To Be Assigned

November 30, 1999

**BOX PATENT APPLICATION** 

Hon. Assistant Commissioner

for Patents

Washington, D. C. 20231

## PRELIMINARY AMENDMENT

Sir:

Prior to examination, please amend the above-identified application as follows:

## **IN THE CLAIMS:**

Claim 2 (amended). Bandage according to Claim 1, [characterized in that] wherein the upper arm part and the forearm part are surrounded by an encapsulating material.

Claim 3 (amended).

Bandage according to Claim 1, [characterized in that]

wherein the edges of the upper arm part, [and/or] forearm or both are thin or conically shaped.

Claim 4 (amended). Bandage according to Claim 1, [characterized in that] wherein profiled recesses can be worked into the upper arm part and exert a partial strengthening action.

Claim 5 (amended). Bandage according to Claim 1, [characterized in that] wherein profiled recesses can be worked into the forearm part and exert a partial strengthening action.

Claim 6 (amended). Bandage according to Claim 1, [characterized in that] wherein the forearm part has a hand guide or hand-securing means.

Claim 7 (amended). Bandage according to Claim 1, [characterized in that] wherein the upper arm part is fixed ventrally to the forearm in the area of the wrist by means of a support strap which runs from the shoulder to the neck area.

Claim 8 (amended). Bandage according to Claim 1, [characterized in that] wherein the support strap comprises a partial padding in the area of transition from the cervical spine to the shoulder girdle.

Claim 9 (amended). Bandage according to Claim 1, [characterized in that]

wherein the support strap is designed partially divided in two parts immediately after the attachment point on the shoulder cap.

Claim 10 (amended). Bandage according to Claim 1 [characterized in that] wherein the holding strap runs from the forearm part, starting from the hand region, dorsally in the lumbar area to the distal upper arm and laterally encloses the latter from posterior to anterior.

Claim 11 (amended). Bandage according to Claim 1, [characterized in that] wherein the straps are made of a laminated foam or a laminated nonwoven fabric.

Claim 12 (amended). Bandage according to Claim 1, [characterized in that] wherein the straps have a high padding effect and, with loading of about 50 N, have a preferred longitudinal expansion of <35%[, particularly preferably a longitudinal expansion of <10%].

Claim 13 (amended). Method for producing a bandage according to <u>Claim 1</u> [at least one of the preceding claims, characterized in that] <u>wherein</u> the upper arm part and the forearm part [which] are made of a starting material which contains at least a proportion of thermoplastic fibres or components, [preferably to at least 10% by weight,] <u>and</u> are thermoformed to the shape of the body part on which they are to be used.

Claim 14 (amended). Method according to Claim 13, wherein said starting [at

least one of the preceding claims, characterized in that the] material is a thermoformable nonwoven fabric, woven fabric, knitted fabric, foil, foam, [and/or a] thermoformable plastic with low rigidity or a combination thereof.

Claim 15 (amended). Method according to <u>Claim 13</u>, <u>wherein</u> [at least one of the preceding claims,] the <u>starting</u> material comprises a two-layer or multi-layer laminate, of which at least one layer is thermoformable.

Claim 16 (amended). Method according to <u>Claim 13</u>, <u>wherein</u> [at least one of the preceding claims, characterized in that] the <u>starting</u> material is heated to thermoformability and is then shaped using a positive mould, [and/or] negative mould <u>or both</u>.

Claim 17 (amended). Method according to <u>Claim 13</u>, <u>wherein</u> [at least one of the preceding claims, characterized in that] the <u>starting</u> material is heated to its thermoformability point and is shaped between a positive mould and a negative mould.

Claim 18 (amended). Method according to <u>Claim 13</u>, <u>wherein</u> [at least one of the preceding claims, characterized in that] the <u>starting</u> material is heated to its thermoformability point and formed in heated moulds.

Claim 19 (amended). Method according to <u>Claim 13</u>, <u>wherein</u> [at least one of the preceding claims, characterized in that] the <u>starting</u> material has been thermoformed

to individual body sizes.

Please add the following:

-- 20. Bandage according to Claim 12, wherein said longitudinal expansion is <10%.--

## **REMARKS**

The preliminary amendment is being filed to eliminate multiple dependency, and to conform the claims to conventional format.

## **ADDITIONAL FEE**

Please charge any insufficiency of fees, or credit any excess, to Deposit Account No. 14-1263.

Respectfully submitted,

NORRIS, McLAUGHLIN & MARCUS, P.A.

William C. Gerstenzang

Reg. No. 27,552

WCG:kts

660 White Plains Road Tarrytown, New York 10591-5144 (914) 332-1700

# Delers

## 428 Rec'd PCT/PTO 0 1 DEC 1999

## Beiersdorf Aktiengesellschaft Hamburg

## Description

5

## Bandage for the arm with enclosure for the shoulder

The invention relates to a bandage for the arm with an enclosure for the shoulder and, if appropriate, an integrated hand guide.

10

15

20

25

30

35

Depending on their design and on the indications for which they are intended, orthopaedic bandages exert a fixing, guiding, bracing and/or supporting action on the extremities of the human body.

These medical bandages must have a three-dimensional shape which corresponds to the anatomical circumstances in order to be able to act externally on the human body with a form fit and a force fit.

Medical bandages of this kind are produced by cutting out blanks from planar material, for example neoprene, knitted fabrics or woven fabrics.

The anatomically appropriate shape is obtained via the shape of the blanks or darts, for example with gussets, and subsequent joining together of the blanks, as is also customary in articles of clothing.

The joining together can be done by sewing, gluing or other conventional methods. The great disadvantage of these bandages is that the exact anatomical fit can be achieved only with difficulty and there are a large number of connection points, for example seams. These connection points change the properties of the material used, and there is the danger of pressure points on the skin.

This risk occurs most often in the case of compression stockings and bandages for burns. The bandages for burns usually have a large number of seams, for example in the region of the female breast and in the facial region, and these often lead to pressure points.

Another possible way of producing medical bandages is shaped knitting with flat knitting machines or circular knitting machines. However, this method is limited in terms of the possibility of shaping and the choice of material. In particular, only two-dimensional shaping is possible. The third dimension can only be achieved by subsequent sewing, in other words with rather undesirable seams. The production is complicated.

Bandages are also known in which foam rubber is deformed under compression moulding to different thicknesses. In this way, as a result of the different density of the foam after deformation, the elastic properties of the material can be locally altered. Such a bandage is described, for example, in WO 95/32690.

A correct fit to the anatomical shape is not achieved in this way.

It is moreover known to shape thermoplastic plate material anatomically correctly to give orthopaedic ortheses and prostheses of suitable form. These materials, for example polyethylene (HDPE), polypropylene or a PP copolymer, have a thermoplastic deformation range of about 170°C to 250°C and are substantially rigid after cooling, so that they cannot be used for medical bandages.

15

20

25

30

35

10

5

DE-P-43 14 785 discloses a bandage system particularly intended for acromioclavicular luxations and lateral fractures of the clavicle. The bandage system is made up of a tube part which receives the forearm and upper arm and which is made of a fabric which is radially elastic but which is essentially non-stretchable in the longitudinal direction, a support band, a holding band, closure members which are provided on the said bands for forming holding loops, and a tightening strap. Such a bandage is suitable for achieving a diminution of the presented indications, but it is very complicated to produce. Moreover, because of the tubular construction, it is often difficult for the patient to fit the bandage without pain.

The object of the invention was therefore to make available a bandage which, by means of an explicit shape fit, ensures secure and stable fixation of the shoulder and of the upper arm and does not have the cited disadvantages of the prior art.

This object is achieved with a bandage as defined in Claim 1. The subclaims concern advantageous refinements of the bandage and methods for producing the shaped parts from which the bandages are formed.

Accordingly, the bandage for the shoulder and upper arm region comprises an anatomically shaped upper arm part which receives the upper arm, and an anatomically shaped forearm part which receives the

35

forearm, the upper arm part being designed in the shape of a half shell and having a cap-like recess for receiving the shoulder joint, and the forearm part being designed in the shape of a half shell and having an enclosure for the elbow joint.

- In addition, the upper arm part and the forearm part are connected to one another in an adjustable manner. Finally, a support strap is arranged on the upper arm part and a holding strap is arranged on the forearm part in order to fix the bandage according to the invention on the body.
- The starting material for producing the upper arm part and the forearm part is preferably a thermoformable nonwoven fabric, a thermoformable foam and/or a thermoformable plastic with low rigidity, the starting material comprising at least 10% by weight of thermoformable material.
- Such starting materials are distinguished by the fact that on the one hand they are soft, and yet, on the other hand, they have sufficient shape stability and a low weight.

The upper arm part and the forearm part are advantageously surrounded by an encapsulating material.

In addition, the edges of the upper arm part and/or of the forearm part are preferably thin or conical. These edges can be produced by welding or sewing.

In a preferred embodiment, profiled recesses are worked into the upper arm part and/or the forearm part and exert a partial strengthening action.

In a further advantageous embodiment, the forearm part has a hand guide or hand-securing means.

If appropriate, the hand guide can be individually shortened, depending on the therapy and the indication, in order to ensure an optimum fit.

The upper arm part is preferably fixed ventrally to the forearm in the area of the wrist by means of a support strap which runs from the shoulder to the neck area, and the support strap can comprise a partial padding in the area of transition from the cervical spine to the shoulder girdle. The partial padding has the function of distributing the occurring loads evenly over the surface. In addition, the support strap is designed partially divided in two parts, preferably immediately after the attachment point on the shoulder

cap, so as to be able to be fixed both ventrally and also dorsally on the thorax.

The holding strap advantageously runs from the forearm part, starting from the hand region, dorsally in the lumbar area to the distal upper arm and laterally encloses the latter from posterior to anterior.

The straps can be fixed, for example, using velcro closures or press studs.

The straps, that is to say the support strap and the holding strap, are preferably made of a laminated foam or a laminated nonwoven fabric.

Finally, it has proven particularly advantageous if the straps have a high padding effect and, with loading of about 50 N, have a preferred longitudinal expansion of <35%, particularly preferably a longitudinal expansion of <10%.

The upper arm part and the forearm part are preferably connected to one another in an adjustable manner.

- The upper arm part and the forearm part can in this case be connected to one another by means of a velcro closure, press studs or seams. An adjustable connection is provided in particular to meet the individual lengths of the extremities and thereby to improve the shape fit efficiency.
- The bandage according to the invention serves in particular as a post-traumatic and post-operative special bandage for injuries in the shoulder and upper arm area, for example distorsions, rotator injuries, periarthritis humeroscapularis, luxations of the shoulder joint, fractures of the shoulder blade and subcapitular fractures of the humerus, fractures of the head of the upper arm and fractures of the shaft of the upper arm.

A special bandage of this kind must have the characteristics according to the invention in order to be able to act correctly for the indication:

- an explicit shape fit in order to ensure a secure and stable fixation of the shoulder and of the upper arm.
  - a well enclosed shoulder joint with corresponding fixation transition to the thoracic area.

Depending on the indication, fixation of the forearm with an integrated hand guide is also necessary in order to substantially guarantee success of treatment. In the same way as with conventional plaster cast therapy, one or two joints of an affected joint are always bridged in order to ensure effective therapy.

The fixation of the forearm also provides additional relief of the shoulder joint, which has a positive effect on the muscles and ligaments and rules out irritation of the nerve structures involved.

- These criteria are satisfied by using two three-dimensionally shaped moulded parts, namely an upper arm part and a lower arm part, which correspond to the anatomical circumstances of the arm and of the shoulder.
- The open, half-shell structure also permits straightforward and painless application of the bandage according to the invention. This is a particular advantage, especially as the patient can apply the bandage himself.

By using shaped parts, the bandage has few if any seams or connection points, so that there is scarcely any further risk of pressure points on the skin or in the area of the bone structures.

The upper arm part and the forearm part, hereinafter referred to simply as shaped parts, for producing the bandage according to the invention are obtained by three-dimensional adaptation of a starting material, which contains at least a proportion of thermoplastic fibres or components, preferably to at least 10% by weight, to the shape of the body part on which they are to be used.

The starting material is preferably a thermoformable nonwoven fabric, a thermoformable foam and/or a thermoformable plastic of low rigidity. Possible plastics having such low rigidity are polyethylene (LDPE), polypropylene and mixtures of the said polymers. In addition, these starting materials can be mixed with other copolymers.

The starting material is also preferably a thermoformable woven fabric or knitted fabric in which elastic fibres or components can be incorporated. The use of a thermoformable foil is also possible.

35

25

5

The materials listed can be made elastic by incorporation of, for example, elastane or elstodiene.

The starting material is also preferably connected to form two-layer or multi-layer laminates, of which at least one layer is thermoformable, and the lamination is carried out using generally known methods, for example lining.

A shaped part can advantageously be produced by starting material, which has been cut to the appropriate shape fit, being heated to the thermoplastic softening point, and this starting material then being pressed to the required shape by means of a positive mould and/or negative mould which is designed corresponding to the anatomical circumstances of the particular body part.

15

20

10

5

The shaped part is also advantageously produced by the starting material, which has been cut to the appropriate shape fit, being heated to the thermoplastic softening point and pressed to the required shape between a positive mould and a negative mould, which are designed corresponding to the anatomical circumstances of the particular body part.

The heating can be carried out using heatable moulds, or by means of the starting material first being suitably heated in an oven and only then shaped in the moulds.

25

30

35

To individually configure the shaped parts, it is necessary to determine the anatomical measurements of the relevant body parts of the patient concerned. This can be done using a computer-aided measurement method, for example scanning, or by simple manual measurement. In addition, an impression of the body part can be taken with wax or plaster. The latter in particular facilitates the production of correspondingly designed positive and negative moulds.

If shaped parts are needed in very large batch numbers, generally conventional anatomical measures can be used to produce the necessary shapes.

The shaped parts according to the invention can be produced easily and inexpensively because they do not have to be joined together or shape-

knitted from a large number of blanks in order to achieve the required shape fit.

A particularly advantageous embodiment of the bandage according to the invention is described below with reference to a number of figures, without thereby unnecessarily restricting the invention.

- Figure 1 shows the upper arm part and the forearm part in a side view,
- Figure 2 shows the upper arm part and the forearm part from the front,
- 10 Figure 3 shows the bandage, comprising upper arm part and forearm part and connection arrangements and straps, and
  - Figure 4 shows the bandage according to the invention applied on a patient.

15 In Figure 1, the upper arm part 1 and the forearm part 2 are represented in a side view.

The upper arm part 1 is in this case designed as a half shell in such a way that it provides an excellent fit to the anatomical circumstances of the right upper arm and the right shoulder of the patient, since the cap-shaped recess 11 is able easily to receive the shoulder joint. The shoulder is here enclosed at the same time as the upper arm in a half shell.

The forearm part 2 is likewise designed as a half shell and adapted to the anatomical circumstances of the right forearm, so that it can perfectly receive or enclose the right elbow joint of the patient within the recess 21.

In the area of the hand, the forearm part 2 has a hand part 22 which serves for fixing the hand and at the same time for supporting the wrist. The fingers are also guided in the hand part 22.

In Figure 2, the upper arm part 1 and the forearm part 2 are represented as viewed into the recesses 11 and 21, respectively. The width of the upper arm part 1 is adapted to the measurements of the shoulder of the patient so that the upper arm part 1 sits firmly on the shoulder, but without exerting pressure. The same applies to the forearm part 2. The diameter of the forearm part 2 is chosen according to the measurements of the wrist, then widens in the area of the forearm musculature and finally narrows again so that the elbow joint is supported in the area of the recess.

The bandage 100 shown in Figure 3 is made up essentially of the upper arm part 1 and the forearm part 2, which are connected to one another in a

15

20

substantially flexible manner via an appropriately shaped connection strap 5. The connection strap 3 is secured on the upper arm part 1 by means of velcro closures, and the connection to the forearm part 1 is effected by a press stud 52. The securing by velcro closures 51 ensures that the bandage can be adapted to the individual circumstances of the patient's arm.

The upper arm part 1 is fixed ventrally to the forearm in the area of the wrist by a support strap 4 which runs from the shoulder to the neck area.

10 The support strap 4 is fixed by means of a velcro closure 41.

The forearm part 2 is fixed with a holding strap 5 which, starting from the hand region, runs dorsally in the lumbar area to the distal upper arm. The holding strap 5 is secured by a velcro closure 51.

The whole strap system together secures the position of the bandage on the patient.

Finally, Figure 4 shows how the bandage 100 according to the invention is applied on the right shoulder and right forearm of the patient. Starting from the patient's wrist, the holding strap 5 runs behind his back and is guided round the right upper arm in a loop and fixed to the holding strap 5 itself, namely by means of the velcro closure 51, behind the patient's back.

#### **Patent Claims**

1. Bandage for the shoulder and upper arm area, comprising an anatomically shaped upper arm part which receives the upper arm, and an anatomically shaped forearm part which receives the forearm,

the upper arm part being designed in the shape of a half shell and having a cap-like recess for receiving the shoulder joint, and

the forearm part being designed in the shape of a half shell and having an enclosure for the elbow joint, and

the upper arm part and the forearm part being connected to one another in an adjustable manner, and a support strap being arranged on the upper arm part and a holding strap being arranged on the forearm part.

- 2. Bandage according to Claim 1, characterized in that the upper arm part and the forearm part are surrounded by an encapsulating material.
  - 3. Bandage according to Claim 1, characterized in that the edges of the upper arm part and/or forearm part are thin or conically shaped.

4. Bandage according to Claim 1, characterized in that profiled recesses can be worked into the upper arm part and exert a partial strengthening action.

- 5. Bandage according to Claim 1, characterized in that profiled recesses can be worked into the forearm part and exert a partial strengthening action.
- 6. Bandage according to Claim 1, characterized in that the forearm part has a hand guide or hand-securing means.
  - 7. Bandage according to Claim 1, characterized in that the upper arm part is fixed ventrally to the forearm in the area of the wrist by means of a support strap which runs from the shoulder to the neck area.

8. Bandage according to Claim 1, characterized in that the support strap comprises a partial padding in the area of transition from the cervical spine to the shoulder girdle.

35

5

10

20

- 9. Bandage according to Claim 1, characterized in that the support strap is designed partially divided in two parts immediately after the attachment point on the shoulder cap.
- 10. Bandage according to Claim 1, characterized in that the holding strap runs from the forearm part, starting from the hand region, dorsally in the lumbar area to the distal upper arm and laterally encloses the latter from posterior to anterior.
- 10 11. Bandage according to Claim 1, characterized in that the straps are made of a laminated foam or a laminated nonwoven fabric.
- 12. Bandage according to Claim 1, characterized in that the straps have a high padding effect and, with loading of about 50 N, have a preferred longitudinal expansion of <35%, particularly preferably a longitudinal expansion of <10%.</li>
- 13. Method for producing a bandage according to at least one of the preceding claims, characterized in that the upper arm part and the forearm part which are made of a starting material which contains at least a proportion of thermoplastic fibres or components, preferably to at least 10% by weight, are thermoformed to the shape of the body part on which they are to be used.
- 25 14. Method according to at least one of the preceding claims, characterized in that the material is a thermoformable nonwoven fabric, woven fabric, knitted fabric, foil, foam and/or a thermoformable plastic with low rigidity.
- 30 15. Method according to at least one of the preceding claims, the material comprises a two-layer or multi-layer laminate, of which at least one layer is thermoformable.
- 16. Method according to at least one of the preceding claims, 35 characterized in that the material is heated to thermoformability and is then shaped using a positive mould and/or negative mould.

- 17. Method according to at least one of the preceding claims, characterized in that the material is heated to its thermoformability point and is shaped between a positive mould and a negative mould.
- 5 18. Method according to at least one of the preceding claims, characterized in that the material is heated to its thermoformability point and formed in heated moulds.
- 19. Method according to at least one of the preceding claims,10 characterized in that the material has been thermoformed to individual body sizes.

#### **Abstract**

Bandage for the shoulder and upper arm area, comprising an anatomically shaped upper arm part which receives the upper arm, and an anatomically shaped forearm part which receives the forearm, the upper arm part being designed in the shape of a half shell and having a cap-like recess for receiving the shoulder joint, and the forearm part being designed in the shape of a half shell and having an enclosure for the elbow joint, the upper arm part and the forearm part being connected to one another in an adjustable manner, and a support strap being arranged on the upper arm part and a holding strap being arranged on the forearm part.




Figure 1




Figure 2




Figure 3




Figure 4

## COMBINATION DECLARATION & POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled "Bandage for the arm with enclosure for the shoulder" the specification of which is attached hereto.

	-OR-				
	was filed on	as			
	Application Seria	al No ar	nd was amended		
			understand the contents of the lendment referred to above.	above ide	entified specification,
			ation which is material to the exa egulations §1.56(a).	amination	of this application in
or pat	ent or inventor's	certificate listed be	Title 35, United States Code, §1 low and have also identified bel date before that of the application	ow any fo	oreign application for
F	Prior Foreign Appli	cation(s)		Priority (	Claimed
	197 24 322.3 (Number)	Germany (Country)	10/06/1997 (Day/Month/Yr. Filed)	[X] yes	[ ] no
_	(Number)	(Country)	(Day/Month/Yr. Filed)	[X] yes	[ ] no
			United States Code, §120 of ar		

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

PCT/EP98/03168	<u> 28/05/1998</u>	pending	
(Application Serial No.)	(Filing Date)	(Status)	
		(patented, pending, abandoned)	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punished by fine or imprisonment, or both under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

1-00

`....

8

**POWER OF ATTORNEY:** As a named Inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Arnold Sprung, Reg. No. <u>17.232</u>; Nathaniel D. Kramer, Reg. No. <u>25,350</u>; Ira J. Schaefer, Reg. No. <u>26,802</u>, and Esther Steinhauer, Reg. No. <u>40,255</u> all of 120 White Plains Road, Tarrytown, New York 10591; Kurt G. Briscoe, Reg. No. <u>33,141</u>; William C. Gerstenzang, Reg. No. <u>27,552</u>; Carmella A O'Gorman, Reg. No. <u>33,749</u> and Stephen G. Ryan, Ref. No. <u>39,015</u> all of 660 White Plains Road, Tarrytown, New York 10591-5144, my attorneys with full power of substitution and revocation

## **Send Correspondence To:**

**Direct Telephone Calls To:** 

Sprung Kramer Schaefer & Briscoe 660 White Plains Road Tarrytown, N. Y. 10591-5144

(914) 332-1700

Full Name Of Sole or First Inventor	Inventor's Signature		Date
Dr. Stefan Bodenschatz	Helm Bo	schild	45/44/45
Residence Beereubug 6 K <del>urt-Schumacher-Straße 11</del> , D-21614 Bu <u>xtehude</u> , Ger		Citizenship German	<u>'</u>
Post Office Address Belfluhar, 6 Kurt-Schumacher-Straße 11, D-21614 Buxtehude, Ger	many he		
Full Name Of Second Inventor	Inventor's Signature	10	Date 1. Lag
Thorsten Herzberg	Thank	list	15/11/44
Residence Langenhorner Chaussee 399, D-22419 Hamburg, Ger	many 10 E×	German	/
Post Office Address Langenhorner Chaussee 399, D-22419 Hamburg, Ger	many		
Full Name Of Third Inventor	Inventor's Signature		Date
Residence		Citizenship	
Post Office Address			
Full Name Of Fourth inventor	Inventor's Signature		Date
Residence	1	Citizenship	
Post Office Address			
Full Name Of Fifth Inventor	Inventor's Signature		Date
Residence	<u>.                                    </u>	Crtizenship	
Post Office Address		I	
Full Name Of Sixth Inventor	Inventor's Signature		Date
Residence		Citizenship	
Post Office Address			
Full Name Of Seventh Inventor	Inventor's Signature		Date
Residence		Citizenship	
Post Office Address			
<u></u>			